


CURVES CAC2000

SERIES A-C 2000

CLOSED COUPLE & FRAME MOUNTED CENTRIFUGAL PUMP PERFORMANCE CURVES - 60 HZ



150 200

80

CUBIC METERS PER HOUF

1750 RPM		1750 RPM		1160 RPM		1160 RPM	
Pump Size And Type	Page #						
1.5x1.5x9	3	4x3x11	11	2x1.5x6.5	19	6x6x13S	28
2.5x2x6.5L	3	4x3x13	12	2x1.5x9	20	8x6x9.5	28
2.5x2x6.5S	4	4x4x11	12	3x2.5x9	20	8x6x11	29
2.5x2x9L	4	6x4x9	13	3x2.5x11	21	8x6x13	29
2.5x2x9S	5	6x4x13	13	3x2.5x13	21	10x8x13	30
2x1.5x6.5	5	6x6x9.5	14	3x2x10	22	3500 RPM	
2x1.5x9	6	6x6x11	14	3x2x11	22	1.5x1.5x9	31
3x2.5x9	6	6x6x13S	15	4x3x6.5	23	2.5x2x6.5L	31
3x2.5x11	7	6x6x13L	15	4x3x9	23	2.5x2x6.5S	32
3x2.5x13	7	8x6x9.5	16	4x3x11	24	2.5x2x9L	32
3x2x6.5L	8	8x6x11	16	4x3x13	24	2.5x2x9S	33
3x2x6.5S	8	8x6x13	17	4x4x11	25	2x1.5x6.5	33
3x2x9	9	10x8x13	17	6x4x9	25	2x1.5x9	34
3x2x10	9	1160 RPM		6x4x13	26	3x2.5x9	34
3x2x11	10	1.5x1.5x9	18	6x6x9.5	26	3x2x6.5L	35
4x3x6.5	10	2.5x2x6.5L	18	6x6x11	27	3x2x6.5S	35
4x3x9	11	2.5x2x6.5S	19	6x6x13L	27	3x2x9	36
						3x2x10	36
						4x3x6.5	37
						4x3x9	37

TABLE OF CONTENTS

USEFUL PUMP FORMULAS


Pressure (PSI)	=	Head (Feet) x Specific Gravity 2.31	
Head (Feet)	=	Pressure (PSI) x 2.31 Specific Gravity	
Vacuum (Inches of Mercury)	=	Dynamic Suction Lift (Feet) x .883 x Specific Gravity	
Horsepower (Brake)	=	GPM x Head (Feet) x Specific Gravity 3960 x Pump Efficiency	
Horsepower (Water)	=	GPM x Head (Feet) x Specific Gravity 3960	
Efficiency (Pump)	=	Horsepower (Water) Horsepower (Brake) x 100 Per Cent	
NPSH	=	Positive Factors – Negative Factors	

Affinity Laws: Effect of change of speed or impeller diameter on centrifugal pumps.


	GPM Capacity	Ft. Head	BHP
Impeller Diameter Change	$Q_2 = \frac{D_2}{D_1} Q_1$	$H_2 = \left(\frac{D_2}{D_1}\right)^2 H_1$	$P_2 = \left(\frac{D_2}{D_1}\right)^3 P_1$
Speed Change	$Q_2 = \frac{RPM_2}{RPM_1} Q_1$	$H_2 = \left(\frac{RPM_2}{RPM_1}\right)^2 H_1$	$P_2 = \left(\frac{RPM_2}{RPM_1}\right)^3 P_1$

Where Q = GPM, H = Head, P = BHP, D = Impeller Dia., RPM = Pump Speed

1750 RPM PUMP CURVES





PERFORMANCE CHARACTERISTIC CURVE



0


1750 RPM PUMP CURVES








CAPACITY, CUBIC METERS/HR

0












6







1750 RPM PUMP CURVES

PERFORMANCE CHARACTERISTIC CURVE








10





CAPACITY, CUBIC METERS/HR

















































CAPACITY, CUBIC METERS/HR





















50%

Т

F

3500 RPM PUMP CURVES





CAPACITY, CUBIC METERS/HR

CAPACITY, U.S. GALLONS PER MINUTE

N.P.S.H. REQUIRED

ŀ





Xylem |'zīləm|

The tissue in plants that brings water upward from the roots;
a leading global water technology company.

We're 12,700 people unified in a common purpose: creating innovative solutions to meet our world's water needs. Developing new technologies that will improve the way water is used, conserved, and re-used in the future is central to our work. We move, treat, analyze, and return water to the environment, and we help people use water efficiently, in their homes, buildings, factories and farms. In more than 150 countries, we have strong, long-standing relationships with customers who know us for our powerful combination of leading product brands and applications expertise, backed by a legacy of innovation.

For more information on how Xylem can help you, go to www.xyleminc.com



Xylem Inc. 2881 East Bayard Street Seneca Falls, NY 13148 Phone: (866) 325-4210 Fax: (888) 322-5877 www.gouldswatertechnology.com